



HIGH PRECISION PRESSURE CALIBRATOR

MODEL : PCAL 1300/1



PVP - 01



Carrying case



Introduction

Exact pressure measurement and monitoring are must in applications crucial to operational safety of machinery and industrial installations.

Regular inspection of the pressure gauges / sensor / transmitters / indicators used in these applications is absolutely essential for economic and technical - safety reasons and is already prescribed as obligatory in many sectors.

Applications

- ☐ Energy - Production and energy -Distribution sectors
- ☐ Glass, Ceramic, Semi conductor industries
- ☐ Steel material processing industries
- ☐ Calibrators laboratories etc.,.

Description

“SANSEL” PCAL 1300 / 1 is a Micro controller based precision pressure calibrators generates true reference pressure. Connect the gauge to be calibrated in the calibrator. Set the pressure using respective pump when stabilization.

Technical Specifications

Model	PCAL 1300 / 1 (Pneumatic)
Display	128 x 64 COG Graphic LCD with White LED Back light
Range (bar)	- 0.9 to 1 bar
Pressure media	Air
Resolution (bar)	6 digit user selectable
Accuracy	± 0.05% FS
Pressure pump	PVP - 01
Instrument port (at pump)	3/8" BSP Female
Test Port (at pump)	1/4" BSP Female
Instrument Port	3/8" BSP Male
Pump dimension in mm (Approx.)	230 x 220 x 70 (H x W x D)
Instrument dimension in mm	100 x 100 x 55 (W x H x D)
Instrument Weight	400gms (Approx.)
Stability time	1 to 2 mins
Pressure units * (selectable)	bar, mbar, MPa, kPa, Pa, PSI, kg/cm ² , inHg, cmHg, mmHg, mH ₂ O, ftH ₂ O, inH ₂ O, cmH ₂ O, mmH ₂ O
Pressure Zero	One touch zero provided on front key
Pressure Peak	Maximum & minimum with user reset option
Pressure overflow	FS X 2 (Max.)
Pressure burst	FS X 3 (Max.)
Temp.Measure	RTD -PT 100 (2,3,4, wire selectable)
Temp. Range	-199.999 to 850.000
mA Measure	0-24 mA (scalable)
Display scale	-99999 to 99999 counts (for mA measure input)
Switch test	Provided
Display Hold	One touch hold provided on front key
Power Supply	9V DC ±5% / 600 mAh Rechargeable battery with battery life 20 hours without backlight (or) 9V DC adapter / 230V AC supply operated
Pc Interface (Optional)	RS-485(2 wire) (Note : connect to PC using USB to RS 485 convertor supplied along with PC software)
Pc Software (Optional)	Windows based semi automatic calibration software (optional)

Note: Above Specification change without notice *factory selected units are display which supports to pressure range

Pressure And Vacuum Calibrator Hand Pump – Pneumatic (Low Pressure)

Model	PVP-01
Ranges	-0.9 bar Vacuum to 2 bar Pressure
Medium	Air
Sensitivity / Resolution	0.05 mbar / 0.5 mmWC
Gauge / Indicator Connection Port	3/8" (F) BSP
Test Connection Port	1/4" (F) BSP
Instrument Dimension	230 x 220 x 70 mm (H x W x D)
Instrument Weight (approx.)	1.1 Kg.

Instrument - Standard Delivery

1. 9V DC Battery charger
2. Test certificate

Pump - Standard Delivery

1. Basic Pump
2. Nylon Hose (Length : 1 Meter)
3. Set of Seals
4. Instruction manual
5. Test certificate
6. Standard adopter set – 8 pieces

1/4" BSP(F) X 1/4" BSP (M)

1/8" BSP(F) X 1/4" BSP (M)

1/2" BSP(F) X 1/4" BSP (M)

3/8" BSP(F) X 1/4" BSP (M)

}

BSP

1/8" NPT(F) X 1/4" BSP (M)

1/4" NPT(F) X 1/4" BSP (M)

1/2" NPT(F) X 1/4" BSP (M)

3/8" NPT(F) X 1/4" BSP (M)

}

NPT

Instrument - Optional

1. Pressure / Vacuum pump
2. Set of adapters
3. Temperature sensors
4. Carrying case
5. NABL Calibration certificate

Pump - Optional

1. Pp Carry case
2. Master Pressure Gauge – PCAL 1300 Series, manufactured by Sansel



SANSEL INSTRUMENTS AND CONTROLS SANSEL CALIBRATION LABORATORIES

ISO/IEC 17025 Accredited Calibration Laboratory by NABL CC - 2879
(Thermal, Mechanical, Electro-Technical, Dimension Parameters)

1 / 46 , 3rd Main road, Ganga Nagar, MMDA Colony , Maduravoyal , Chennai - 600 095. INDIA
☎ +91 44 2378 3951, 📞 +91 72999 72085 / 86 / 93, 📠 +91 98401 49928 ✉ enquiry@ sansel.net

🌐 www.sansel.net

🌐 www.sansel.in

🌐 www.sansel.co.in

🌐 www.calibrators.in

